



impression[&] XI

TECHNICAL DATA	
LED SOURCE	
LED-Type	Osram Ostar
Lifetime (hours)	50.000h
LED numbers	7
LED colors	RGBW
OPTICAL SYSTEM	
Fixed optics	7° (interchangeable)
MOVEMENT	
Resolution	8 - 16 bit
Position Feedback	yes
Pan	660°
Tilt	360°
Continous movem.	360° continous pan & tilt movement
CONTROL	
Control modes	Normal, Compressed, High Resolution
Display	Illuminated graphic LCD
Protocol	DMX-512
Cooling	Temperature controlled, convection cooling, overheating protection
EFFECTS	
Dimmer	0 - 100% electronic
Shutter	Max. 14 Hz electronically
CONNECTORS	
Signal connection	XLR 5-pin, input & output
Power input	Neutrik Powercon, input & output

OPERATING CONDITIONS	
Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	100 Watt
Fuse	20mm T 2A
Max ambient temp.	45° C
Operating position	Any
MOUNTING OPTIONS	
Standing	Rubber feet
Hanging	M10 sockets for clamps and halfcouplers
Safety wire attachm.	2 Eyelets
SHIPPING	
Single fixture	Cardboard
Tourpack	6-way, 12-way incl.flightcase and halfcoupl.
HOUSING COLORS	
Standard colors	Black
Optional	Special colors on request
DIMENSIONS & WEIGHT	
Length	195mm
Width	140mm
Height (head vert.)	255mm
Weight	3,1kg