



impression[&] X4

TECHNICAL DATA	
LED SOURCE	
LED-Type	Osram Ostar
Lifetime (hours)	50.000h
LED numbers	19
LED colors	RGBW, CwWw
OPTICAL SYSTEM	
Minimum zoom	7°
Maximum zoom	50°
MOVEMENT	
Resolution	8 - 16 bit
Position Feedback	yes
Pan	660°
Tilt	280°
CONTROL	
Control modes	Normal, Compressed, High Resolution
Display	Illuminated graphic LCD, backlit buttons
Protocol	DMX-512
Cooling	Temp. controlled, overheating protection
EFFECTS	
Dimmer	0 - 100% electronic
Shutter	Max. 25 Hz electronically
Color temp.filter	Electronic 2.500K - 10.000K
Internal effects	LED Macro Effects, Color presets
CONNECTORS	
Signal connection	XLR 5-pin
Power input	Neutrik Powercon

OPERATING CONDITIONS	
Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	350 Watt
Fuse	20mm T 5A
Max ambient temp.	45° C
Operating position	Any
MOUNTING OPTIONS	
Standing	Removable baseplate with belt brackets
Hanging horizontal	Adjustable bar for sideway truss installation (optional)
Hanging vertical	M10 sockets for clamps and halfcouplers, omegabacket (optional)
Safety wire attachm.	2 Eyelets
SHIPPING	
Single fixture	Cardboard
Tourpack	4-way, 6-way incl.flightcase and halfcoupler
HOUSING COLORS	
Standard colors	Black
Optional	White, special colors on request
DIMENSIONS & WEIGHT	
Length	242mm
Width	340mm
Height (head vert.)	385mm
Weight	7,5kg