



impression[&] X4L

TECHNICAL DATA

LED SOURCE	
LED-Type	Osram Ostar
Lifetime (hours)	50.000h
LED numbers	37
LED colors	RGBW
OPTICAL SYSTEM	
Minimum zoom	7°
Maximum zoom	50°
Beamshape	Motorized
MOVEMENT	
Resolution	8 - 16 bit
Position Feedback	yes
Pan	660°
Tilt	250°
CONTROL	
Control modes	Normal, Compressed, High Resolution, Pixel-Mapping
Display	Illuminated graphic LCD, backlit buttons, self charging buffer battery
Protocol	DMX-512, RDM
Cooling	Temp. controlled, overheating protection
EFFECTS	
Dimmer	0 - 100% electronic
Shutter	Max. 25 Hz electronically
Color temp.filter	Electronic 2.500K - 10.000K
Internal effects	LED Macro Effects

CONNECTORS	
Signal connection	XLR 5-pin, input & output
Power input	Neutrik PowerCon
OPERATING CONDITIONS	
Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	900 Watt
Fuse	20mm T 5A
Max ambient temp.	45° C
Operating position	Any
MOUNTING OPTIONS	
Standing	Removable baseplate with belt brackets
Hanging horizontal	Adjustable bar for sideways truss installation (optional)
Hanging vertical	M10 sockets for clamps and halfcouplers, omegabacket (optional)
Safety wire attachm.	2 Eyelets
SHIPPING	
Single fixture	Cardboard
Tourpack	4-way, incl.flightcase and halfcoupler
HOUSING COLORS	
Standard colors	Black
Optional	Special colors on request
DIMENSIONS & WEIGHT	
Length	430mm
Width	185mm
Height (head vert.)	530mm
Weight	17kg