



impression X4S

TECHNICAL DATA

LED SOURCE

LED-Type Osram Ostar

Lifetime (hours) 50.000h

LED numbers 7

LED colors RGBW

OPTICAL SYSTEM

Minimum zoom 7°

Maximum zoom 50°

MOVEMENT

Position Feedback yes

Pan 660°

Tilt 250°

CONTROL

Control modes Normal, Compressed, High Resolution

Display Illuminated graphic LCD

Protocol DMX-512

Cooling Temp. controlled, overheating protection

EFFECTS

Dimmer 0 - 100% electronic

Shutter Max. 10 Hz electronically

Color temp.filter Electronic 2.500K - 10.000K

Internal effects LED Macro Effects, Color presets

CONNECTORS

Signal connection XLR 5-pin, input & output

Power input Neutrik Powercon, input & output

OPERATING CONDITIONS

Mains voltage 100-240 VAC / 50-60Hz

Power Watt@230V 200 Watt

Fuse 20mm T 5A

Max ambient temp. 45° C

Operating position Any

MOUNTING OPTIONS

Standing Rubber feet

Hanging M10 sockets for clamps and halfcouplers

Safety wire attachm. 2 Eyelets

SHIPPING

Single fixture Cardboard

Tourpack 4-way, 8-way incl.flightcase and halfcoupler

HOUSING COLORS

Standard colors Black

Optional Special colors on request

DIMENSIONS & WEIGHT

Length 155mm

Width 220mm

Height (head vert.) 310mm

Weight 5,8kg