



# impression<sup>&</sup> X4 XL

## TECHNICAL DATA

### LED SOURCE

LED-Type	Osram Ostar
Lifetime (hours)	50.000h
LED numbers	55
LED colors	RGBW

### OPTICAL SYSTEM

Minimum zoom	7°
Maximum zoom	50°

### MOVEMENT

Resolution	8 - 16 bit
Position Feedback	yes
Pan	540°
Tilt	250°

### CONTROL

Control modes	Normal, Compressed, High Resolution,
Display	Illuminated graphic LCD
Protocol	DMX-512
Cooling	Temp. controlled, overheating protection

### EFFECTS

Dimmer	0 - 100% electronic
Shutter	Max. 10 Hz electronically
Color temp.filter	Electronic 2.500K - 10.000K
Internal effects	LED Macro Effects, color presets

### CONNECTORS

Signal connection	XLR 3-pin & XLR 5-pin, input & output
Power input	Neutrik PowerCon

## OPERATING CONDITIONS

Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	1200 Watt
Fuse	20mm T 12A
Max ambient temp.	45° C
Operating position	Any

## MOUNTING OPTIONS

Standing	Removable baseplate with belt brackets
Hanging horizontal	Adjustable bar for sideways truss installation (optional)
Hanging vertical	M10 sockets for clamps and halfcouplers, omegabacket (optional)
Safety wire attachm.	2 Eyelets

## SHIPPING

Single fixture	Cardboard
Tourpack	2-way, incl.flightcase and halfcoupler

## HOUSING COLORS

Standard colors	Black
Optional	Special colors on request

## DIMENSIONS & WEIGHT

Length	550mm
Width	200mm
Height (head vert.)	515mm
Weight	24kg