




TECHNICAL DATA

LED SOURCE

LED	Osram
Lifetime (hours)	50.000h
Color temperature	2700K - 5000K
Light output	3500lm (clear lens)

OPTICAL SYSTEM

Clear window		
Lensed window		120°
Frosted window		

CONTROL

Dimming	2 circuits (cold and/or warm)
LED colors	Cool White, Warm White, Red, Blue
Dimming interface	0 - 10V

OPERATING CONDITIONS

Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	32,5 Watt
Ambient temp.	-20° - +45°
Protection	IP67

CONNECTION

Cable entry	3 entry holes for cable, luminaire shipped with 3pc cable glands with hex nut and 2pc blind plugs
-------------	---

MOUNTING OPTIONS

Fixed flat installation	9pc M8 mounting holes on backside
Flexible installation	Mounting set optional

HOUSING

Material	Aluminum
Color	Uncoated (special colors on request)

DIMENSIONS & WEIGHT

Length	438,5mm
Width	121,5mm
Height (head vert.)	82,5mm
Weight	3,5kg

DIFFERENT MODELS

ILU30-WK14-F	Cool White, Warm White, clear window
ILU30-WK14-D	Cool White, Warm White, frosted window
ILU30-WR17-D	Red, Warm White, frosted window
ILU30-WB18-D	Blue, Warm White, frosted window
ILU30-WW11-D	Warm White, Warm White, frosted window
ILU30-KK44-D	Cool White, Cool White, frosted window
ILU30-WK14-L	Cool White, Warm White, clear lenses
ILU30-WR17-L	Red, Warm White, clear lenses
ILU30-WB18-L	Blue, Warm White, clear lenses
ILU30-WW11-L	Warm White, Warm White, clear lenses
ILU30-KK44-L	Cool White, Cool White, clear lenses